



Technical specifications

Power supply: 24V DC
 Power consumption: 30W (max)
 Fusing: built in trip switch with push button reset
 CE approved

Performance

21 days preservation
 Resealing time: 1 – 5 seconds
 Each system is pre-set to operate at altitudes between 0 – 500m; for locations above this level please refer to the manufacturer or your local dealer



What's included with each system

20x still wine eStoppers,
 6x sparkling wine stoppers
 A pre-set CO2 regulator
 5m length of CO2 hose
 Power supply configured to your region, complete with 1.5m cable
 Mounting kit
 12 month warranty

Sourcing CO2: The only item that needs sourcing locally is a food-grade CO2 supply to support sparkling wine preservation. We will be happy to recommend preferred suppliers in your market, please contact us directly.

Product	Model No.	Wine Preservation		Height		Width		Depth		Weight	
		Still	Sparkling	mm	inch	mm	inch	mm	inch	kg	lb
Tower	BC06	Yes	Yes	510	20	120	4.72	135	5.31	6.0	10.58
Tower - Still wine only	BC05S	Yes	No	510	20	120	4.72	135	5.31	5.4	11.90
Tower - Sparkling wine only	BC05C	No	Yes	510	20	120	4.72	135	5.31	4.4	9.70

For Portable and Bespoke Edition models please call: **610-889-4900** or email: sales@bermaramerica.com